

Sec. 6-151. Cargo lifts. With adopted changes 8-15-02

(a)

Permit required. No cargo lift shall be installed at any location within the village without obtaining a cargo lift permit and paying a permit fee in the amount provided in the village fee schedule.

(b)

Use for human transport prohibited; must be located outside living areas. A cargo lift shall be used for the transport of goods only and not to be used for human transport. A cargo lift must be installed on the exterior of a building and may not enter any living area of a building.

(c)

Caging and locking requirements. A cargo lift must have a lower caged or fenced area constructed of lattice, louvers, chainlink fencing or equivalent, with openings no larger than three and onehalf (3 1/2) inches. Solid wall material is prohibited. The caged area must be from the ground level to the top of the cage and have a lockable gate which must be kept locked at all times when not in use. It must also be equipped with a keyed electrical lockout. The upper landing must have an additional lockable gate which must be kept locked at all times when not in use.

(d)

Warning signs. Warning signs stating "WarningCargo Lift In Use" shall be posted on all gates, entries and areas reachable to a cargo lift. In addition, the cage or car of the cargo lift shall have attached a sign stating "Not For Human Transport."

(Code 1994, §§ 3.1102—3.1105; Ord. No. 021301, § 2, 2192013)

(e)

Caging / fencing option – Instead of having the caging or fencing for protection from bodily injury a descending lift a company manufactured pressure sensitive switch may be installed to reverse or stop the descending lift platform. Approved by Council March 15, 2016